

View Online at <https://aerobasegroup.com/nsn/5930-01-043-2400>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

0.575 inches

**Overall Height:**

2.020 inches

**Overall Width:**

0.535 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.575 inches

**Body Width:**

0.535 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

0.810 inches

**Actuator Width:**

0.300 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

28.0 dc and 115.0 ac

**Mounting Surface To Terminal End Distance:**

0.740 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver and terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0