# NSN 5930-01-043-3005

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-043-3005

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

2.375 inches

#### **Overall Height:**

1.312 inches

#### **Overall Width:**

1.625 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.375 inches single actuator

#### **Overall Diameter:**

1.312 inches

#### **Nonturn Device Radius:**

0.562 inches at 3: 00 o'clock

## Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 3: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

### Pole Quantity:

2 1st section rear

#### **Throw Quantity:**

5 2nd section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

115.0 ac at sea level

## Switch Actuator Indexing Position Quantity:

5 single actuator

### Shaft Type:

Round single actuator

### **Terminal Type:**

Tab, solder lug

# NSN 5930-01-043-3005

Rotary Switch - Page 2 of 2



**Contact Switching Action:** Breaks before makes 2nd section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0