

View Online at <https://aerobasegroup.com/nsn/5930-01-043-3006>

**Thread Class:**

2b

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Bushing Length:**

0.170 inches

**Body Length:**

0.572 inches

**Body Width:**

0.364 inches

**Body Height:**

0.562 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.093 inches

**Actuator Height:**

0.440 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Sonar signal processing sys, an/sqq-2 (v); sturgeon class ssn (637); spruance class dd (963); forrestal class cv; los angeles class ssn (688); virginia class cgn (41); ticonderoga class cg (47); nimitz class cvn; aircraft, ac--130h, mc-130h, ec-130e, hc-130

**Mounting Surface To Terminal End Distance:**

0.800 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A053a0