

View Online at <https://aerobasegroup.com/nsn/5930-01-043-3006>

Thread Class:

2b

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

0.170 inches

Body Length:

0.572 inches

Body Width:

0.364 inches

Body Height:

0.562 inches

Actuator Style:

Round

Actuator Diameter:

0.093 inches

Actuator Height:

0.440 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Sonar signal processing sys, an/sqq-2 (v); sturgeon class ssn (637); spruance class dd (963); forrestal class cv; los angeles class ssn (688); virginia class cgn (41); ticonderoga class cg (47); nimitz class cvn; aircraft, ac--130h, mc-130h, ec-130e, hc-130

Mounting Surface To Terminal End Distance:

0.800 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0