

View Online at <https://aerobasegroup.com/nsn/5930-01-043-3521>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.812 inches

**Body Length:**

0.628 inches

**Body Height:**

0.260 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

0.200 inches

**Actuator Height:**

0.330 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac

**End Application:**

Ticonderoga class cg (47), nimitz class cvn, spruance class dd (963), avenger class mcm, oliver perry class ffg, kidd class ddg, arleigh burke class ddg, whidbey island class lsd, los angeles class ssn (688), general purpose electronic test equipment-gpete.

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Terminals silver

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0