

View Online at <https://aerobasegroup.com/nsn/5930-01-043-3521>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.812 inches

Body Length:

0.628 inches

Body Height:

0.260 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

0.200 inches

Actuator Height:

0.330 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

125.0 ac

End Application:

Ticonderoga class cg (47), nimitz class cvn, spruance class dd (963), avenger class mcm, oliver perry class ffg, kidd class ddg, arleigh burke class ddg, whidbey island class lsd, los angeles class ssn (688), general purpose electronic test equipment-gpete.

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminals silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0