NSN 5930-01-043-4877

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-043-4877 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Body Length:** 0.500 inches **Body Width:** 0.200 inches **Unthreaded Mounting Hole Diameter:** 0.091 inches **Actuator Length:** 0.500 inches **Actuator Style:** Leaf **Actuator Width:** 0.090 inches **Actuator Free Position Height:** 0.325 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 5.0 grams **Switch Actuating Force:** 30.0 grams **Actuator Movement:** Between 0.115 pretravel inches and 0.025 overtravel inches and 0.035 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac **Terminal Type And Quantity:** 3 turret Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-01-043-4877 Sensitive Switch - Page 2 of 2



Fiig:

A053a0