

View Online at <https://aerobasegroup.com/nsn/5930-01-043-5894>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.623 inches

Overall Height:

1.000 inches

Overall Width:

1.500 inches

Flat Height:

0.195 inches single actuator and 0.199 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.562 inches single actuator and 0.593 inches single actuator

Nonturn Device Radius:

0.280 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Base single mounting facility and threaded hole single mounting facility

Features Provided:

Cam actuated

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, two positions momentary single switch single section in-line

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section in-line

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Detent Rotational Torque Range:

+20.000/+35.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0