

View Online at <https://aerobasegroup.com/nsn/5930-01-043-5907>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Bushing Length:

0.380 inches

Body Length:

1.810 inches

Body Width:

0.640 inches

Body Height:

0.640 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.145 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.360 inches

Actuator Free Position Height:

0.920 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

17.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.200 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0