

View Online at <https://aerobasegroup.com/nsn/5930-01-043-5910>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof and shock proof

Body Length:

0.740 inches

Body Width:

0.740 inches

Body Height:

Between 1.180 inches and 1.250 inches

Case Material:

Plastic

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Height:

Between 1.310 inches and 1.380 inches

Actuator Width:

0.740 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Panel count 43689

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Special Features:

High-shock and moisture-proof mounting rack

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

12 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0