

View Online at <https://aerobasegroup.com/nsn/5930-01-043-8931>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Industrial use

Actuator Style:

Round

Actuator Diameter:

0.326 inches

Actuator Free Position Height:

0.500 inches

Housing Height:

2.047 inches

Housing Length:

3.062 inches

Housing Width:

1.000 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

0.187 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.437 inches

Maximum Voltage Rating In Volts:

460.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

Between 10.0 ounces and 20.0 ounces

Actuator Movement:

Between 0.172 pretravel inches and 0.219 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0