

View Online at <https://aerobasegroup.com/nsn/5930-01-043-8933>

**Body Style:**

Hole mounted

**Overall Length:**

Between 1.370 inches and 1.390 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.120 inches and 1.130 inches

**Overall Height:**

Between 0.671 inches and 0.751 inches

**Overall Width:**

Between 0.515 inches and 0.545 inches

**Body Length:**

Between 0.935 inches and 0.945 inches

**Body Width:**

Between 0.515 inches and 0.545 inches

**Body Height:**

Between 0.280 inches and 0.300 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.136 inches and 0.140 inches

**Actuator Length:**

Between 0.275 inches and 0.285 inches

**Actuator Height:**

Between 0.016 inches and 0.046 inches

**Actuator Width:**

Between 0.215 inches and 0.225 inches

**Actuator Position-action Relationship:**

Left position maintained and right position maintained

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac

**End Application:**

Trainer, cockpit 23259

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

**Special Features:**

UL and CSA listed

**Precious Material And Location:**

Terminals and contact surfaces silver

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0