

View Online at <https://aerobasegroup.com/nsn/5930-01-043-8933>

Body Style:

Hole mounted

Overall Length:

Between 1.370 inches and 1.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.120 inches and 1.130 inches

Overall Height:

Between 0.671 inches and 0.751 inches

Overall Width:

Between 0.515 inches and 0.545 inches

Body Length:

Between 0.935 inches and 0.945 inches

Body Width:

Between 0.515 inches and 0.545 inches

Body Height:

Between 0.280 inches and 0.300 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.136 inches and 0.140 inches

Actuator Length:

Between 0.275 inches and 0.285 inches

Actuator Height:

Between 0.016 inches and 0.046 inches

Actuator Width:

Between 0.215 inches and 0.225 inches

Actuator Position-action Relationship:

Left position maintained and right position maintained

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Trainer, cockpit 23259

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 1.500 amperes resistive ac

Special Features:

UL and CSA listed

Precious Material And Location:

Terminals and contact surfaces silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0