NSN 5930-01-043-8937

View Online at https://aerobasegroup.com/nsn/5930-01-043-8937

Push Switch - Page 1 of 2

Body Style:Panel mount



Hazardous Locations/environmental Protection: Dustproof and explosion proof **Body Length:** 0.740 inches **Body Width:** 0.740 inches **Body Height:** 2.760 inches **Case Material: Plastic Actuator Length:** 0.740 inches **Actuator Style:** Rectangular **Actuator Width:** 0.740 inches **Actuator Color:** Green single actuator and red single actuator **Illuminated Actuator Color:** Green single actuator and red single actuator

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

...............................

Features Provided:

Rfi shielding

Panel

Nonpile-up Contact Arrangement:

Maximum Voltage Rating In Volts:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Terminals gold

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-01-043-8937

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0