

View Online at <https://aerobasegroup.com/nsn/5930-01-044-1617>

Inside Diameter:

0.062 inches single connection

Overall Length:

5.375 inches

Outside Diameter:

0.250 inches single connection

Overall Height:

2.000 inches

Overall Width:

3.375 inches

Body Length:

5.000 inches

Distance Between Mounting Facility Centers:

3.750 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+2.00/+24.00 actuation point pounds per square inch

Contact Stimulus Rating:

10.00 actuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Barbed, unthreaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0