NSN 5930-01-044-1617

Pressure Switch - Page 1 of 2

Inside Diameter:

Overall Length: 5.375 inches

Outside Diameter:

0.062 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-01-044-1617

0.250 inches single connection
Overall Height:
2.000 inches
Overall Width:
3.375 inches
Body Length:
5.000 inches
Distance Between Mounting Facility Centers:
3.750 inches
Pressure Switch Type:
Differential
Mounting Method:
Bracket
Contact Action Stimulus:
Increase
Proof Pressure:
30.00 pounds per square inch
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
25.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point adjustable, preset
Contact Adjustment Range:
+2.00/+24.00 actuation point pounds per square inch
Contact Stimulus Rating:
10.00 actuation point pounds per square inch and 2.00 differential point pounds per square inch
Contact Voltage Rating In Volts:
480.0 ac at sea level single voltage
Pressure Connector Type:
Barbed, unthreaded external single connection
Frequency In Hertz:
60.0 single voltage

NSN 5930-01-044-1617

Pressure Switch - Page 2 of 2



Media For Which Designed:
Gas
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0