## NSN 5930-01-044-2383

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-2383

| Overall Length:   |
|---|
| 4.875 inches  |
| Overall Height:   |
| 4.500 inches  |
| Overall Width:  |
| 2.875 inches  |
| Body Height:  |
| 2.500 inches  |
| Bulb Length:  |
| 3.000 inches  |
| Bulb Diameter:  |
| 0.688 inches  |
| Longest Horizontal Distance Between Mounting Centers:   |
| 2.406 inches  |
| Shortest Horizontal Distance Between Mounting Centers:  |
| 1.750 inches  |
| Longest Vertical Distance Between Mounting Centers:   |
| 3.281 inches  |
| Tempurature Sensing Element Type:   |
| Bulb  |
| Operating Tempurature Rating:   |
| 195.0 degrees fahrenheit  |
| Mounting Method:  |
| Bracket   |
| Features Provided:  |
| Electrical access port  |
| Contact Action Stimulus:  |
| Decrease  |
| Mounting Facility Pattern:  |
| Isosceles triangle  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally open, momentary action   |
| Terminal Type:  |
| Screw   |
| Contact Load Current Rating:  |
| 3.2 amperes resistive load first voltage  |
| Contact Adjustability:  |
| Deactuation point adjustable and actuation point adjustable   |
| Contact Adjustment Range:   |
| +90.00/+165.00 actuation point degrees fahrenheit and +86.00/+161.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type:  |

Contact Adjustificht Type

External deactuation point screw and external actuation point screw

## NSN 5930-01-044-2383

Thermostatic Switch - Page 2 of 2



| Contact Voltage Rating In Volt      |
|-------------------------------------|
| 550.0 ac at sea level first voltage |
| Media For Which Designed:           |
| Gas or liquid                       |
| Style Designator:                   |
| Rectangular                         |
| Shelf Life:                         |
| N/a                                 |
| Unit Of Measure:                    |
|                                     |
| Demilitarization:                   |
|                                     |

No Fiig: A048b0