## NSN 5930-01-044-4034

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-4034

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

**Overall Length:** 

2.022 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.375 inches single actuator

**Overall Diameter:** 

1.750 inches

**Individual Section Quantity:** 

2

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

4 1st section rear

**Throw Quantity:** 

4 1st section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

**Contact Load Current Rating:** 

1.0 amperes resistive load ac at sea level

## NSN 5930-01-044-4034

Rotary Switch - Page 2 of 2



| P | racions | Matarial | And  | Location: |
|---|---------|----------|------|-----------|
| _ | recious | wateriai | Allu | LOCALION. |

Terminals silver and contact surfaces silver

**Precious Material:** 

Silver

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0