Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-4139

# Hazardous Locations/environmental Protection:

Dustproof and moisture resistant and shock proof and vibration proof

## **Overall Length:**

1.760 inches

# **Overall Height:**

1.780 inches

#### **Overall Width:**

1.150 inches

#### **Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

# Individual Section Quantity:

# 2

#### Longest Horizontal Distance Between Mounting Centers:

1.590 inches single mounting facility

#### Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

#### **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

#### **Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

# Actuator Type:

Thumbwheel all actuators

# **Features Provided:**

Illuminated

#### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Mounting Facility Pattern:**

Four position rectangular single mounting facility

#### Switch Actuator Indexing Position Quantity:

10 all actuators

#### **Terminal Type:**

Printed circuit

#### **Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

#### **Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

# **Contact Arrangement Truth Table:**

Bcd, separate common to not-true bits, 2 pole - 10 positions each section

### Color:

White each indicator marking

#### **Precious Material And Location:**

Contact surfaces gold

Code Indicating Wheel Switch - Page 2 of 2



**Precious Material:** 

Gold

# Style Designator:

Rectangular inline indicating

# Test Data Document:

81349-mil-s-22710 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-s-22710/15 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A052b0