

View Online at <https://aerobasegroup.com/nsn/5930-01-044-4491>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Moisture resistant

Body Diameter:

0.720 inches

Bushing Length:

0.625 inches

Body Length:

1.000 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Free Position Height:

0.875 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

144.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.125 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Cable has 2 leads from switch cut and terminated under shrink tubing, cable length 24.000 inches

Thread Series Designator:

Uns

Terminal Type And Quantity:

1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0