## NSN 5930-01-044-5688

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-5688
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
2.190 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.950 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 ampere
inductive ac and 1.000 amperes lamp ac

## **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

## NSN 5930-01-044-5688

Push Switch - Page 2 of 2



Termina	I Type	And C	Juantity	<b>,</b> :

18 socket, integrated wire termination

**Specification Data:** 

81349-mil-s-22885/77 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0