

View Online at <https://aerobasegroup.com/nsn/5930-01-044-8729>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Corrosion resistant and moisture resistant and corrosion proof and vibration resistant

Overall Length:

0.531 inches

Overall Height:

1.279 inches

Overall Width:

0.511 inches

Bushing Length:

0.354 inches

Body Length:

0.531 inches

Body Width:

0.283 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.410 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Mounting Surface To Terminal End Distance:

0.515 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces gold and contacts silver and contact surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A053a0