

View Online at <https://aerobasegroup.com/nsn/5930-01-044-8729>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Corrosion resistant and moisture resistant and corrosion proof and vibration resistant

**Overall Length:**

0.531 inches

**Overall Height:**

1.279 inches

**Overall Width:**

0.511 inches

**Bushing Length:**

0.354 inches

**Body Length:**

0.531 inches

**Body Width:**

0.283 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.410 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

115.0 ac and 29.0 dc

**Mounting Surface To Terminal End Distance:**

0.515 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:**

Terminal surfaces gold and contacts silver and contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A053a0