

View Online at <https://aerobasegroup.com/nsn/5930-01-044-9250>

Thread Class:

2b all threaded hole

Inside Diameter:

0.125 inches single connection

Overall Length:

2.870 inches

Body Length:

2.030 inches

Overall Diameter:

1.420 inches

Pressure Switch Type:

Absolute

Mounting Facility Circle Radius:

1.000 inches

Operating Temperature Rating:

Between -54.0 degrees celsius and 71.0 degrees celsius

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

40 all threaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

50.00 pounds per square inch absolute

Thread Size:

0.112 inches all threaded hole

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

15.30 actuation point pounds per square inch absolute and 13.30 deactuation point pounds per square inch absolute and 2.00 differential point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, unthreaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0