

View Online at <https://aerobasegroup.com/nsn/5930-01-044-9251>

Thread Class:

3a all threaded stud

Overall Length:

4.400 inches

Overall Diameter:

5.000 inches

Pressure Switch Type:

Differential

Mounting Facility Circle Radius:

2.080 inches

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case and electrical access port

Thready Qty Per Inch (tpi):

32 all threaded stud

Contact Action Stimulus:

Increase

Proof Pressure:

15.00 pounds per square inch absolute

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.50/+30.00 actuation point inches of water and +0.50/+27.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point hex nut and external actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Unf all threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0