## NSN 5930-01-044-9271

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-044-9271

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.336 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Actuator Length:

## 0.620 inches

Actuator Style:

Rectangular

#### Actuator Height:

0.340 inches

## Actuator Width:

0.620 inches

#### Actuator Color:

Amber single actuator and natural single actuator

#### **Illuminated Actuator Color:**

White single actuator and white single actuator

#### Actuator Inscription:

Cal 0 single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.756 inches

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

## **Features Provided:**

Actuator seal and horizontal split lens and rfi shielding

## Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac



# NSN 5930-01-044-9271

Push Switch - Page 2 of 2



## **Precious Material And Location:**

Contacts gold

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0