

View Online at <https://aerobasegroup.com/nsn/5930-01-044-9271>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.336 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.340 inches

Actuator Width:

0.620 inches

Actuator Color:

Amber single actuator and natural single actuator

Illuminated Actuator Color:

White single actuator and white single actuator

Actuator Inscription:

Cal 0 single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.756 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens and rfi shielding

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0