NSN 5930-01-044-9277

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-9277

| Body Style: |
|---|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Explosion proof and humidity resistant |
| Overall Length: |
| 3.380 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.340 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| Natural single actuator |
| Illuminated Actuator Color: |
| White single actuator |
| Actuator Inscription: |
| Yes 7 single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 2.950 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal and full display lens and rfi shielding |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac

NSN 5930-01-044-9277

Push Switch - Page 2 of 2



| Precious Material And Location: |
|---------------------------------------|
| Contacts gold |
| Terminal Type And Quantity: |
| 1 socket, integrated wire termination |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0