NSN 5930-01-044-9658

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-9658

Overall Length:
3.850 inches
Overall Height:
2.270 inches
Overall Width:
2.720 inches
Body Diameter:
3.220 inches
Unthreaded Mounting Hole Diameter:
0.200 inches
Distance Between Mounting Facility Centers:
1.000 inches
End Application:
Washing machine ldry 81306
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
10.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+2.50/+8.75 actuation point inches of water and +1.20/+4.10 deactuation point inches of water
Contact Adjustment Type:
External deactuation point shaft and external actuation point shaft
Contact Voltage Rating In Volts:
250.0 ac at sea level first voltage
3
Media For Which Designed:
•
Media For Which Designed:

NSN 5930-01-044-9658

Pressure Switch - Page 2 of 2



Otal-	D!	
Style	Desigr	nator:

Cylindrical w/lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0