NSN 5930-01-044-9659

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-96
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
Between 2.017 inches and 2.025 inches
Overall Height:
1.300 inches
Overall Width:
1.300 inches
First Flat Length:
0.770 inches single actuator
Flat Height:
0.195 inches single actuator and 0.197 inches single actuator
Shaft Diameter:
$0.247 \ \text{inches} \ \text{single} \ \text{actuator} \ \text{and} \ 0.251 \ \text{inches} \ \text{single} \ \text{actuator}$
Shaft Length:
1.013 inches single actuator
Individual Section Quantity:
1
End Application:
Washing machine lo 81306
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear

Throw Quantity:

5 single section rear

Mounting Method:

Bracket single mounting facility

Contact Voltage Rating In Volts:

250.0 highest ac voltage rating at sea level

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+15.000/+40.000 inch-ounces single actuator

NSN 5930-01-044-9659

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

4.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0