## NIGNI 5030-01-044-0650



Rotary Switch - Page 1 of 2	Group
View Online at https://aerobasegroup.com/nsn/5930-01-044-9659	
Hazardous Locations/environmental Protection:	
Dustproof	
Overall Length:	
Between 2.017 inches and 2.025 inches	
Overall Height:	

1.300 inches

**Overall Width:** 

1.300 inches

First Flat Length:

0.770 inches single actuator

Flat Height:

0.195 inches single actuator and 0.197 inches single actuator

**Shaft Diameter:** 

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

1.013 inches single actuator

**Individual Section Quantity:** 

1

**End Application:** 

Washing machine lo 81306

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

5 single section rear

**Mounting Method:** 

Bracket single mounting facility

**Contact Voltage Rating In Volts:** 

250.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Detent Rotational Torque Range:** 

+15.000/+40.000 inch-ounces single actuator

## NSN 5930-01-044-9659

Rotary Switch - Page 2 of 2



## Switch Actuator Stop Device Type: Fixed stop single actuator Contact Load Current Rating: 4.0 amperes resistive load lowest ac voltage rating at sea level Style Designator: Tap, square frame Shelf Life: N/a Unit Of Measure:

No

Demilitarization:

Fiig:

A052b0