

View Online at <https://aerobasegroup.com/nsn/5930-01-044-9663>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

3.041 inches

Overall Height:

1.313 inches

Overall Width:

1.125 inches

First Flat Length:

0.250 inches 2nd actuator

Flat Height:

0.078 inches 2nd actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.931 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

8 5th section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

120.0 degrees from nonturn device 2nd actuator

Switch Actuator Indexing Position Quantity:

8 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

1.5 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces silver and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0