NSN 5930-01-044-9668

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-044-9668

3.336 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.340 inches
Actuator Width:
0.620 inches
Actuator Color:
Natural single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Select target single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.756 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens and rfi shielding
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

NSN 5930-01-044-9668

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc and 1.000 amperes resistive ac and 500.000 milliamperes inductive ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0