NSN 5930-01-044-9982

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-044-9982
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Corrosion resistant
Overall Length:
0.750 inches
Overall Height:
2.770 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.109 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Green single actuator and red single actuator
Actuator Inscription:
Test test single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.620 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

NSN 5930-01-044-9982

Push Switch - Page 2 of 2



Special Features:
Horizontal split lens
Precious Material And Location
Contacts silver
Terminal Type And Quantity:
6 turret and 5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0