NSN 5930-01-045-0217

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-045-0217 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Body Length:** 0.500 inches **Body Width:** 0.200 inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.091 inches **Actuator Length:** 0.965 inches **Actuator Style:** Leaf **Actuator Width:** 0.090 inches **Actuator Free Position Height:** 0.305 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 3.0 grams **Switch Actuating Force:** 20.0 grams **Actuator Movement:** Between 0.185 pretravel inches and 0.046 overtravel inches and 0.060 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac **Terminal Type And Quantity:** 3 turret Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-045-0217

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0