

View Online at <https://aerobasegroup.com/nsn/5930-01-045-1679>

**Overall Length:**

4.875 inches

**Overall Width:**

2.875 inches

**Body Length:**

4.625 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Capillary Tube Length:**

120.0 inches

**Bulb Length:**

9.000 inches

**Bulb Diameter:**

0.688 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

1.750 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**Temperature Sensing Element Type:**

Capillary tube-bulb

**Operating Temperature Rating:**

238.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

3.2 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+90.00/+165.00 actuation point degrees fahrenheit and +90.00/+165.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

550.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0