NSN 5930-01-045-3057



| Rotary Switch - Page 1 of 2 |
|---------------------------------------------------------------|
| View Online at https://aerobasegroup.com/nsn/5930-01-045-3057 |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 3.520 inches |
| Overall Height: |
| 1.740 inches |
| Overall Width: |
| 2.120 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.189 inches single mounting facility |
| Individual Section Quantity: |
| 2 |
| Knob Manufacturer Code: |
| 27192 |
| Knob Manufacturer Part Number: |
| 53-1160 |
| Longest Horizontal Distance Between Mounting Centers: |
| 1.620 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.250 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 each section rear |
| Throw Quantity: |
| 2 each section rear |
| Mounting Method: |
| Unthreaded hole single mounting facility |
| Features Provided: |
| Actuator knob |
| Contact Voltage Rating In Volts: |
| 440.0 highest ac voltage rating at sea level |

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

NSN 5930-01-045-3057

Rotary Switch - Page 2 of 2

No Fiig: A052b0



| Switch Actuator Stop Device Type: |
|-------------------------------------------------------------------------|
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 75.0 milliamperes inductive load highest ac voltage rating at sea level |
| Style Designator: |
| Tap, circuit selector |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |