NSN 5930-01-045-4323

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-045-4323

Thread Class:
2b all threaded hole
Overall Length:
1.830 inches
Overall Height:
2.888 inches
Overall Width:
2.372 inches
Body Height:
2.880 inches
Distance Between Mounting Facility Centers:
1.750 inches
Capillary Tube Length:
36.0 inches
Bulb Length:
5.660 inches
Bulb Diameter:
0.250 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Mounting Method:
Bracket and threaded hole
Features Provided:
Capillary tube end seal connection
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.138 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
2 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
25.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+376 00/+396 00 actuation point degrees fabrepheit and +390 00/+410 00 deactuation point degrees fabrepheit

NSN 5930-01-045-4323

Thermostatic Switch - Page 2 of 2

Fiig: A048b0



Contact Adjustment Type:
External deactuation point dial and external actuation point dial
Contact Voltage Rating In Volts:
250.0 ac at sea level first voltage
Media For Which Designed:
Gas
Style Designator:
Rectangular
Thread Series Designator:
Unc all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No