

View Online at <https://aerobasegroup.com/nsn/5930-01-045-4328>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.182 inches

First Flat Length:

0.230 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.270 inches single actuator

Overall Diameter:

Between 0.490 inches and 0.577 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0