## NSN 5930-01-045-7701

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-045-7701

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.400 inches
Body Height:
0.625 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.703 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.290 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
50.0 grams
Switch Actuating Force:
86.0 grams
Actuator Movement:
Between 0.200 pretravel inches and 0.140 overtravel inches and 0.050 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 10.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

## NSN 5930-01-045-7701

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A053a0