

View Online at <https://aerobasegroup.com/nsn/5930-01-045-8716>

Thread Class:

2b single mounting facility

Overall Length:

10.879 inches

Overall Height:

2.750 inches

Overall Width:

2.750 inches

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.938 inches single actuator

Nonturn Device Radius:

0.500 inches at 12: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 12: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0