NSN 5930-01-045-8716

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-045-8716 **Thread Class:** 2b single mounting facility **Overall Length:** 10.879 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 0.938 inches single actuator **Nonturn Device Radius:** 0.500 inches at 12: 00 o'clock **Individual Section Quantity: Nonturn Device Type:** Pin at 12: 00 o'clock **Longest Horizontal Distance Between Mounting Centers:** 1.500 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 each section rear **Throw Quantity:** 2 each section rear **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 120.0 ac at sea level **Mounting Facility Pattern:** Two position in-line single mounting facility **Switch Actuator Indexing Position Quantity:** 4 single actuator **Shaft Type:** Round single actuator **Terminal Type:**

Clip

NSN 5930-01-045-8716

Rotary Switch - Page 2 of 2



Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
15.0 amperes resistive load ac at sea leve
Precious Material And Location:
Contact surfaces gold and contacts silver
Precious Material:
Gold and silver
Style Designator:
Tap, square frame
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A052b0