NSN 5930-01-046-0108

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-046-0108

Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Dustproof and explosion proof
Overall Length:
1.336 inches
Overall Height:
2.359 inches
Overall Width:
1.015 inches
Bushing Length:
0.469 inches
Body Length:
1.336 inches
Body Width:
1.015 inches
Actuator Style:
Round
Actuator Diameter:
0.240 inches
Actuator Height:
0.687 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Color:
Natural single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Vweapon system-iwo jima class lph; spruance class dd (963); nimitz class cvn; kidd class ddg; ticonderoga class cg (47); oliver perry
class ffg; virginia class cgn (41); forrestal class cv; whidbey island class lsd; wasp class lhd
Mounting Surface To Terminal End Distance:
1.203 inches
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

NSN 5930-01-046-0108

Toggle Switch - Page 2 of 2



Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 25.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Special Features:

Weapon system essential

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms14002 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0