NSN 5930-01-046-0238

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-046-0238

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Actuator Length:

1.750 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.063 inches

Housing Length:

4.938 inches

Housing Width:

2.938 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.813 inches

Maximum Voltage Rating In Volts:

115.0 ac and 115.0 dc

Inclosure Type:

Fully enclosed

Switch Release Force:

45.0 inch-ounces

Switch Actuating Force:

150.0 inch-ounces

Actuator Movement:

80.0 pretravel degrees and 7.0 overtravel degrees and 3.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 6.000 amperes resistive ac

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-046-0238 Sensitive Switch - Page 2 of 2

Fiig: A053a0

