

View Online at <https://aerobasegroup.com/nsn/5930-01-046-3392>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.516 inches

Case Material:

Metal

Actuator Length:

0.470 inches

Actuator Style:

Leaf

Actuator Width:

0.125 inches

Actuator Free Position Height:

Between 0.335 inches and 0.365 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Test set mk562 16623

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

6.0 ounces

Actuator Movement:

Between 0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0