

View Online at <https://aerobasegroup.com/nsn/5930-01-046-3392>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.781 inches

**Body Width:**

0.250 inches

**Body Height:**

0.516 inches

**Case Material:**

Metal

**Actuator Length:**

0.470 inches

**Actuator Style:**

Leaf

**Actuator Width:**

0.125 inches

**Actuator Free Position Height:**

Between 0.335 inches and 0.365 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Test set mk562 16623

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

0.5 ounces

**Switch Actuating Force:**

6.0 ounces

**Actuator Movement:**

Between 0.094 pretravel inches and 0.047 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0