

View Online at <https://aerobasegroup.com/nsn/5930-01-046-4634>

Thread Class:

2a single mounting facility

Thread Length:

0.220 inches single mounting facility

Overall Length:

3.460 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.249 inches single actuator

Shaft Length:

0.990 inches single actuator

Overall Diameter:

1.470 inches

Nonturn Device Radius:

0.530 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Push to turn

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.468 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Rotor Through Connection Quantity:

4 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section front

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 3.0 amperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0