

View Online at <https://aerobasegroup.com/nsn/5930-01-046-4637>

**Overall Length:**

7.938 inches

**Overall Height:**

2.875 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches single mounting facility

**Individual Section Quantity:**

7

**Longest Horizontal Distance Between Mounting Centers:**

1.875 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.688 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

2 each section periphery

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

600.0 highest dc voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

46.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

8.0 amperes resistive load highest ac voltage rating at sea level and 6.0 amperes inductive load highest ac voltage rating at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0