

View Online at <https://aerobasegroup.com/nsn/5930-01-046-5495>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Body Width:**

0.750 inches

**Body Height:**

0.750 inches

**Switch Actuator Quantity:**

1

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.090 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

White single actuator

**Illuminated Actuator Color:**

White single actuator

**Actuator Inscription:**

Sim, pwr single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

2.620 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0