## NSN 5930-01-046-5497

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-046-5497

## **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Moisture resistant

## **Body Width:**

0.750 inches

## **Body Height:**

0.750 inches

#### Switch Actuator Quantity:

1

#### Actuator Length:

0.620 inches

#### **Actuator Style:**

Rectangular

#### **Actuator Height:**

#### 0.090 inches

Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

White single actuator

#### **Actuator Inscription:**

Pre-, set single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.620 inches

#### Inclosure Type:

Fully enclosed

#### Mounting Method:

Panel

#### **Features Provided:**

Rfi shielding

#### Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac and 7.000 amperes resistive dc and 4.000 amperes

inductive dc and 2.500 amperes lamp dc

## **Precious Material And Location:**

Contacts silver

#### **Terminal Type And Quantity:**

5 tab, solder lug and 6 turret

# NSN 5930-01-046-5497

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

